

AX200		AX2123		AX1216					
Part No.	Material	Emitter Color	Pin	Lens Type	Wave Length λ_p (nm)	At 20mA		View Angle $2\theta_{1/2}$ (deg)	Package Dimension
						Vf (V) Typ.	Iv (mcd) Min		
AX200UIC	---	Orange Red	---	Water Clear	640	2.0	95	110	
AX200UOC	---	Orange	---	Water Clear	610	2.2	95	110	
AX200UYC	---	Yellow	---	Water Clear	595	2.0	200	110	
AX200UGC	---	Green	---	Water Clear	575	2.0	95	110	
AX200ZGC	---	Green	---	Water Clear	520	3.3	190	110	
AX200UBC	---	Blue	---	Water Clear	460	3.50	50	110	
AX2123UIC	---	Orange Red	---	Water Clear	640	2.0	80	150	
AX2123UOC	---	Orange	---	Water Clear	610	2.2	80	150	
AX2123UYC	---	Yellow	---	Water Clear	595	2.0	80	150	
AX2123UGC	---	Green	---	Water Clear	575	2.0	25	150	
AX2123ZGC	---	Green	---	Water Clear	520	3.3	160	150	
AX2123UBC	---	Blue	---	Water Clear	460	3.50	40	150	
AX1216UIC	---	Orange Red	---	Water Clear	640	2.0	80	150	
AX1216UOC	---	Orange	---	Water Clear	610	2.2	80	150	
AX1216UYC	---	Yellow	---	Water Clear	595	2.0	80	150	
AX1216UGC	---	Green	---	Water Clear	575	2.0	25	150	
AX1216ZGC	---	Green	---	Water Clear	520	3.3	160	150	
AX1216UBC	---	Blue	---	Water Clear	460	3.50	40	150	

NOTES:

1. All dimensions are in millimeters.
2. Tolerance is +/- 0.2mm unless otherwise specified
3. Protruded resin under flange is 1.5mm MAX.
4. Specifications are subject to change without notice.