



M339RGW-A

Light Emitting Diode

Description

- I Size : 5mm (T-1 3/4) Round Type.
- I Lens color : White Diffused.
- I Color : Two Color (Red and Green).
- I Lead type : Radial leads.

Main Features

- I Instant light less than 100ns turn on time.
- I Superior resistance to moisture.
- I Low drive current, recommend forward current: IF= 10- 20mA.
- I Cool beam, safe to touch.
- I Common Anode.
- I Reliable and rugged.
- I **Pb-free**

Absolute Maximum Rating TA=25°C					
Parameter	Symbol	Rating		Unit	Notice
Power Dissipation	Pd	Red	80	mW	----
		Green	75		
DC Forward Current	IF	Red	25	mA	
		Green	25		
Pulse Forward Current	IF (PEAK)	Red	100	mA	Duty 1/10 @ 1KHz
		Green	90		
Derating Linear From 50°C		0.4		mA/ °C	
Reverse Voltage	VR	5		V	Under 100uA
Operating Temperature Range	T OPR	-30 to +80		°C	
Storage Temperature Range	T STG	-40 to +80		°C	Humidity should be under 50%
Lead Soldering Temperature	T SOL	260 +/-5		°C	4mm (0.157") from mold body Less then 5 Second



M339RGW-A

Light Emitting Diode

Part Selection Electrical / Optical Characteristics At TA=25°C							
Characteristic	Symbol	Test Condition	Color	Min.	Typ.	Max.	Unit.
Forward Voltage	V _F	I _F =20mA	Red	1.5	1.8	2.4	V
			Green	1.7	2.2	2.6	
Reverse Current	I _R	V _R =5V	Red	—	—	10	uA
			Green	—	—	10	
Luminous Intensity (Note 1)	I _v	I _F =20mA	Red	20	40	60	mcd
			Green	25	50	70	
Peak Emission Wavelength	λ _p	I _F =20mA	Red	655	660	665	nm
			Green	565	568	573	
Spectral Line Half Width	Δλ	I _F =20mA	Red	20	25	30	nm
			Green	25	30	35	
Dominant Wavelength (Note 2)	λ _d	I _F =20mA	Red	635	640	645	nm
			Green	566	572	576	

Note:


1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. The dominant wavelength (λ_d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
3. Forward voltage measurement allowance is +/-0.1V
4. Luminous intensity measurement allowance +/-10%



M339RGW-A

Light Emitting Diode

Package Dimensions




Lens Color	White Diffused		Viewing Angle	70 +/-5 Deg.
Chips Material	D1 (Red)	GaAsP	Emitted Color	Red and Green
	D2 (Green)	GaP	Common Mode	Anode Type

NOTES:

- I All dimensions are in millimeters (inches).
- I Tolerance is ± 0.25 mm (.010") unless otherwise noted.
- I Protruded resin under flange is 1.0mm(.04") max
- I Lead spacing is measured where the leads emerge from the package.
- I Specifications are subject to change without notice.

Typical Electrical / Optical Characteristic Curves At 25°C Ambient Temperature



NOTE:

- I $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- I Clean only in isopropanol, ethanol, Freon TF (or equivalent).
- I When using this product, Please observe the absolute maximum rating and the instructions for use outlined from use of the product, which does not comply with the absolute maximum rating and the instructions included in these specification sheet.
- I **Q.A Outgoing inspection standard:**
Major Defect 0.65 A.Q.L. Minor Defect 1.5 A.Q.L
- I **Lead Forming:**
If forming is required, it must be done before soldering. Form pin leads by securing under 5mm from body and bedding with radio pliers or the equivalent to avoid pressure on resin. When the LED is mounted into a P.C.board, pitch spacing should be aligned to prevent cause any stress to the resin. Any unsuitable stress applied to resin may break bonding wire in LED, which will cause failure.
- I Check at a distance of 30cm from the LED to the eye defects.
- I **Over-current-proof:**
Customer must apply resistor for protection; otherwise slight voltage shift will cause big current change (Burn out will happen).
- I **Parallel connection:**
Customer must apply series resistor in **EACH LED** under parallel connection. Otherwise VF tolerance will cause LED array brightness uneven.
- I Specifications are subject to change without notice.

