

CR052		CR2130		CRM2734					
Part No.	Material	Emitter Color	Pin	Lens Type	Wave Length λ_p (nm)	At 20mA		View Angle $2\theta_{1/2}$ (deg)	Package Dimension
						Vf (V) Typ.	Iv (mcd) Min		
CR052UIC	---	Orange Red	---	Water Clear	640	2.0	120	120	
CR052UOC	---	Orange	---	Water Clear	610	2.2	120	120	
CR052UYC	---	Yellow	---	Water Clear	595	2.0	120	120	
CR052UGC	---	Green	---	Water Clear	575	2.0	45	120	
CR052ZGC	---	Green	---	Water Clear	520	3.3	340	120	
CR052UBC	---	Blue	---	Water Clear	460	3.50	60	120	
CR052UWC	---	White	---	Water Clear	X=0.22~0.38 Y=0.22~0.36	3.50	420	120	
CR2130UIC	---	Orange Red	---	Water Clear	640	2.0	90	120	
CR2130UOC	---	Orange	---	Water Clear	610	2.2	120	120	
CR2130UYC	---	Yellow	---	Water Clear	595	2.0	120	120	
CR2130UGC	---	Green	---	Water Clear	575	2.0	35	120	
CR2130ZGC	---	Green	---	Water Clear	520	3.3	230	120	
CR2130UBC	---	Blue	---	Water Clear	460	3.50	60	120	
CRM2734GARBC	---	Orange Red	---	Water Clear	640	2.00	95	120	
	---	Green	---	Water Clear	520	3.30	190	120	
	---	Blue	---	Water Clear	460	3.50	50	120	
CRM2734GAOBC	---	Orange	---	Water Clear	610	2.20	95	120	
	---	Green	---	Water Clear	520	3.30	190	120	
	---	Blue	---	Water Clear	460	3.50	50	120	

NOTES:

1. All dimensions are in millimeters.
2. Tolerance is +/- 0.2mm unless otherwise specified
3. Protruded resin under flange is 1.5mm MAX.
4. Specifications are subject to change without notice.