

C1530 (1206)			C2432A (1210) DOME LENS			CM1820 (0807)			
Part No.	Material	Emitter Color	Pin	Lens Type	Wave Length $\lambda_p$ (nm)	At 20mA		View Angle $2\theta_{1/2}$ (deg)	Package Dimension
						Vf (V) Typ.	Iv (mcd) Min		
C1530UIC	---	Orange Red	---	Water Clear	640	2.0	125	40	
C1530UOC	---	Orange	---	Water Clear	610	2.2	250	40	
C1530UYC	---	Yellow	---	Water Clear	595	2.0	230	40	
C1530UGC	---	Green	---	Water Clear	575	2.0	63	40	
C1530ZGC	---	Green	---	Water Clear	520	3.3	640	40	
C1530UBC	---	Blue	---	Water Clear	460	3.50	160	40	
C2432AUIC	---	Orange Red	---	Water Clear	640	2.0	900	15	
C2432AUOC	---	Orange	---	Water Clear	610	2.2	1500(Typ)	15	
C2432AUYC	---	Yellow	---	Water Clear	595	2.0	1600(Typ)	15	
C2432AUGC	---	Green	---	Water Clear	575	2.0	175	15	
C2432AZGC	---	Green	---	Water Clear	520	3.3	980	15	
C2432AUBC	---	Blue	---	Water Clear	460	3.50	350	15	
CM1820RGC-1	---	Orange Red	1,2	Water Clear	640	2.00	80	140	
	---	Green	3,4	Water Clear	575	2.00	25	140	
CM1820RGC-2	---	Orange Red	1,2	Water Clear	635	2.00	80	140	
	---	Green	3,4	Water Clear	575	2.00	25	140	
CM1820GBC	---	Green	1,2	Water Clear	520	3.30	160	140	
	---	Blue	3,4	Water Clear	460	3.50	40	140	

**NOTES:**

- All dimensions are in millimeters.
- Tolerance is +/- 0.2mm unless otherwise specified
- Protruded resin under flange is 1.5mm MAX.
- Specifications are subject to change without notice.